

产 品 规 格 书

批 准	审 核	校 核	编 制
纪春华	/	朴致均	郑羿
2018.06.29	/	2018.06.29	2018.06.29

规格书更改履历:

序号	更改内容	履历号	更改时间	责任人
1	新规制定	000	2018.06.29	郑羿


Applications

- Power amplifier application
- High current switching application

Features

- High current : $I_C=2A$
- Complementary pair with KTA3250L

PIN Connection



Ordering Information

Type NO.	Marking	Package Code
KTC4250L	KTC4250 YWW●	TO-92L

DEVICE CODE, YWW(Y : Year code, WW : Weekly code) ● Dalian

Absolute Maximum Ratings

[Ta=25°C]


Characteristic	Symbol	Rating	Unit
Collector-base voltage	V_{CBO}	50	V
Collector-emitter voltage	V_{CEO}	50	V
Emitter-base voltage	V_{EBO}	5	V
Collector current	I_C	2	A
Base current	I_B	0.4	A
Collector Power dissipation	P_C	1	W
	P_C^*	2	W
Junction temperature	T_J	150	°C
Storage temperature range	T_{stg}	-55~150	°C

※ Device mounted on ceramic substrate (250mm² × 0.8t)

KTC4250L

Electrical Characteristics

[Ta=25°C]

Characteristic		Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-emitter breakdown voltage		BV_{CEO}	$I_C=10mA, I_B=0$	50	-	-	V
Collector cut-off current		I_{CBO}	$V_{CB}=50V, I_E=0$	-	-	0.1	μA
Emitter cut-off current		I_{EBO}	$V_{EB}=5V, I_C=0$	-	-	0.1	μA
DC current gain		h_{FE}	$V_{CE}=2V, I_C=0.5A^*$	120	-	240	
		h_{FE}	$V_{CE}=2V, I_C=1.5A^*$	40	-	-	
Collector-emitter saturation voltage		$V_{CE(sat)}$	$I_C=1A, I_B=0.05A^*$	-	-	0.35	V
Base-emitter saturation voltage		$V_{BE(sat)}$	$I_C=1A, I_B=0.05A^*$	-	-	1.2	V
Transition frequency		f_T	$V_{CE}=2V, I_C=50mA$	-	240	-	MHz
Collector output capacitance		C_{ob}	$V_{CB}=10V, I_E=0, f=1MHz$	-	15	-	pF
Switching Time	Turn-on Time	t_{on}	 <p>$I_B = 50mA$ DUTY CYCLE 5%</p>	-	100	-	nS
	Storage Time	t_{stg}		-	300	-	
	Fall Time	t_f		-	50	-	

*: Pulse test: $t_p \leq 300\mu s$, Duty cycle $\leq 2\%$

Electrical Characteristic Curves

Fig. 1 $P_C - T_a$




Fig. 2 $I_C - V_{BE}$




Fig. 3 $I_C - V_{CE}$




Fig. 4 $h_{FE} - I_C$




Fig. 5 $V_{CE(sat)} - I_C$





Fig. 6 $V_{BE(sat)} - I_C$



Electrical Characteristic Curves

Fig. 7 $C_{ob} - V_{CB}$






Fig. 8 Safe Operating Area



Outline Dimension(mm)



SYMBOL	MILLMETERS(mm)			NOTE
	MINIMUM	NOMINAL	MAXIMUM	
A	3.70	3.90	4.10	
A1	1.25	1.45	1.65	
b	0.40	0.50	0.60	
b1	—	—	0.70	
b2	—	—	1.00	
c	0.35	0.45	0.55	
D	4.70	4.90	5.10	
D1	3.70	3.90	4.10	
E	7.80	8.00	8.20	
e	1.27 TYP			
L	13.10	13.50	13.90	
L1	0.90	1.00	1.10	
L2	1.50	1.70	1.90	

The AUK Corp. products are intended for the use as components in general electronic equipment (Office and communication equipment, measuring equipment, home appliance, etc.).

Please make sure that you consult with us before you use these AUK Corp. products in equipments which require high quality and / or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, transportation, combustion control, all types of safety device, etc.). AUK Corp. cannot accept liability to any damage which may occur in case these AUK Corp. products were used in the mentioned equipments without prior consultation with AUK Corp..

Specifications mentioned in this publication are subject to change without notice.